

## Coils ASC

### Standards

- ALCO ASC Coils and cable assemblies conform to Low Voltage Directive



ASC

| Type                   | Part No.       | Voltage | Power Input | Electr. Connection                    | Protection                            |
|------------------------|----------------|---------|-------------|---------------------------------------|---------------------------------------|
| <b>ASC 230V / 50Hz</b> | <b>801 064</b> | AC      | 8 W         | without plug,<br>see cable assemblies | IP65<br>with plug / cable<br>assembly |
| ASC 120V / 50Hz        | 801 063        |         |             |                                       |                                       |
| ASC 24V / 50Hz         | 801 062        |         |             |                                       |                                       |
| ASC 12V                | 801 054        | DC      | 15 W        |                                       |                                       |
| ASC 120V               | 801 050        |         |             |                                       |                                       |
| ASC 230V               | 801 056        |         |             |                                       |                                       |

Note: Coils are delivered with mounting clip.  
Please order cable assemblies separately.



ASC-N15

## Cable Assemblies for ASC Coils

| Type    | Part No. | Temperature Range | Cable length | Wire diameter            | Connector Type |
|---------|----------|-------------------|--------------|--------------------------|----------------|
| ASC-N15 | 804 570  | -25 ..+80°C       | 1,5m         | 3 x 0,75 mm <sup>2</sup> | loose wires    |
| ASC-N30 | 804 571  |                   | 3,0m         |                          |                |
| ASC-N60 | 804 572  |                   | 6,0m         |                          |                |
| ASC-L15 | 804 573  | -50..+80°C        | 1,5m         |                          |                |
| ASC-L30 | 804 574  |                   | 3,0m         |                          |                |
| ASC-L60 | 804 575  |                   | 6,0m         |                          |                |

## Cable Assemblies with 24V DC Chopper Plug

- Enables standard 24V AC Coil to be used for DC applications
- Low power assumption (3W only)
- No MOPD degradation



DS2-N15

| Type    | Part No. | Temperature Range | Cable length | Wire diameter            | Connector Type |
|---------|----------|-------------------|--------------|--------------------------|----------------|
| DS2-N15 | 804 620  | -25 .. +80°C      | 1,5m         | 2 x 0,75 mm <sup>2</sup> | loose wires    |
| DS2-N30 | 804 621  |                   | 3,0m         |                          |                |
| DS2-N60 | 804 622  |                   | 6,0m         |                          |                |

## Other Accessories for Solenoid Valves

| Type        | Part No. | Description  |
|-------------|----------|--|
| X 11981 - 1 | 027 451  | Service tool for 110RB, 240RA, 540RA, 3031         |
| X 13983 -1  | 027 622  | Mounting bracket for 240RA                         |
| X 13740 -1  | 027 600  | Clip for coil                                      |
| PG9 Plug    | 801 012  | Plug according to DIN 43650 with cable gland PG 9  |
| PG11 Plug   | 801 013  | Plug according to DIN 43650 with cable gland PG 11 |