수 신기 채널 별 선택

- 신호램프 _ 위로 - 멈춤 - 아래

1 채널





2 채널

5 채널


1.모델 및 사양

* 수신 기는 각 송신기 ID를 8개 까지 수용이 가능하다.


모델 번호	공급전원	출력 전원	출력 힘	조작방식	기타사양
ERM33F.01000	AC110V/220V 50-60Hz	220VAC/2A	<500W	-리모컨 -수동	주파수 대역: 400 MHz 대역 수신감도: 110dBm 주위 온도: -30~64
ERM33F.02000		220VAC/2A			
ERM36F.01000-01	AC100V-240V 50-60Hz	24VDC/1.5A	≤36W	-리모컨 -수동 -외부입력 태양열 풍속 우적센서등	
ERM36F.02000-02		24VDC/2A	≤48W		케이스등급; IP34
ERM36F.01000-03		24VDC/3A	≤72W		
ERM66F.01000-04	DC24V	24VDC/5A	≤ 120W		

2. 모델 별 결선 도

ERM33F.01000-00




ERM33F.02000-00



ERM36F.01WSR-01


........




송신기 채널 별 선택








....... ERM36F.02WSR-02



...... ERM66F.01WSR-04



1 채널

2 채널

5 채널



